

Asbestos Awareness & Management

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- disturbance of friable asbestos-containing materials
- airborne fibers when disturbed
- airborne asbestos fibers when disturbed
- increased airborne asbestos fiber concentrations
- airborne asbestos fiber release
- in accordance with the requirements of the following paragraphs of this section
- in such manner so as to preclude the dispersion of dust
- 30 days of completion or recompletion of a well, stratigraphic test or core hole
- hot work after an inspection that is free of fire hazards
- at least one additional safety measure that along with the energy-isolating device and tag will provide the equivalent safety available from the use of a lock
- asbestos PEL of 0.1 fiber per cc (8-hour TWA)
- Class I (removal), Class II (removal of non-friable), Class III (repair/maintenance), Class IV (cleanup)
- mandatory requirements of the standard
- informational only and do not create additional obligations
- 29 CFR 1926.1101
- where showers are not provided, that employees wash their hands and face at the end of the work-shift
- the equipment with its typical load on the maximum grade it travels
- surface-operated equipment at underground mines when an MSHA inspector has reasonable cause to believe that the service brake system does not function as required
- the high-voltage trailing cable for damage to the outer jacket
- the mine or nearest mine office from the date the defects are recorded until the defects are corrected
- fiberboard box (4G) or fiber drum (1G) with plastic inner packaging not exceeding 5 kg (11 lbs) and maximum net mass not more than 25 kg (55 lbs)
- third physician to conduct examinations, consultations, laboratory tests and discussions with prior physicians as necessary to resolve disagreement
- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow, procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas
- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- the overall status of implementation of the provisions of this Part relating to the identification, inventory, and removal of underwater obstructions
- activities involving the removal of TSI and surfacing ACM and PACM
- repair and maintenance operations, where ACM, including TSI and surfacing ACM and PACM, is likely to be disturbed

FEDERAL OSHA REQUIREMENTS

- Class I: removal of TSI/surfacing ACM, Class II: removal of non-TSI ACM (flooring, roofing, siding), Class III: repair/maintenance of ACM, Class IV: custodial contact with ACM

29 CFR 1926.1101(e)

- more than one percent asbestos

29 CFR 1926.1101(b)

- Certified Asbestos Abatement Contractor or Supervisor

1926.1101

- certified asbestos abatement contractor or supervisor; class-specific training for all workers

29 CFR 1926.1101

- Written Asbestos Abatement Plan

1926.1101

- removal or encapsulation of materials containing asbestos

29 CFR 1926.1101(a)(2)

- installation of products containing asbestos

29 CFR 1926.1101(a)(4)

- asbestos PEL of 0.1 fiber per cc (8-hour TWA)

29 CFR 1926.1101

- asbestos-containing asphalt roof coatings, cements and mastics

29 CFR 1926.1101(a)(8)

- asbestos spill/emergency cleanup

29 CFR 1926.1101(a)(5)

- the removal of ACM which is not thermal system insulation or surfacing material

29 CFR 1926.1101(b)

- repair and maintenance operations, where ACM, including TSI and surfacing ACM and PACM, is likely to be disturbed

29 CFR 1926.1101(b)

- the removal of TSI and surfacing ACM and PACM

29 CFR 1926.1101(b)

- fiberboard box (4G) or fiber drum (1G) with plastic inner packaging not exceeding 5 kg (11 lbs) and maximum net mass not more than 25 kg (55 lbs)

- in writing or a personal communication between the owner and the recipient or their authorized representatives

29 CFR 1926.1101(k)

COMPANY PROCEDURES

Guy's Construction implements the following procedures for asbestos awareness & management:

- Guy's Construction shall: more than one percent asbestos

29 CFR 1926.1101(b)

- Guy's Construction shall: Certified Asbestos Abatement Contractor or Supervisor

1926.1101

- Guy's Construction shall: certified asbestos abatement contractor or supervisor; class-specific training for all workers

29 CFR 1926.1101

- Guy's Construction shall: Written Asbestos Abatement Plan

1926.1101

- Guy's Construction shall: asbestos PEL of 0.1 fiber per cc (8-hour TWA)

29 CFR 1926.1101

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

California STATE-SPECIFIC REQUIREMENTS (FULL)

- disturbance of friable asbestos-containing materials
- airborne fibers when disturbed
- airborne asbestos fibers when disturbed
- increased airborne asbestos fiber concentrations
- airborne asbestos fiber release
- in accordance with the requirements of the following paragraphs of this section
- in such manner so as to preclude the dispersion of dust
- 30 days of completion or recompletion of a well, stratigraphic test or core hole
- hot work after an inspection that is free of fire hazards
- at least one additional safety measure that along with the energy-isolating device and tag will provide the equivalent safety available from the use of a lock
- asbestos PEL of 0.1 fiber per cc (8-hour TWA)
- Class I (removal), Class II (removal of non-friable), Class III (repair/maintenance), Class IV (cleanup)
- mandatory requirements of the standard
- informational only and do not create additional obligations
- 29 CFR 1926.1101
- where showers are not provided, that employees wash their hands and face at the end of the work-shift
- the equipment with its typical load on the maximum grade it travels
- surface-operated equipment at underground mines when an MSHA inspector has reasonable cause to believe that the service brake system does not function as required
- the high-voltage trailing cable for damage to the outer jacket
- the mine or nearest mine office from the date the defects are recorded until the defects are corrected
- fiberboard box (4G) or fiber drum (1G) with plastic inner packaging not exceeding 5 kg (11 lbs) and maximum net mass not more than 25 kg (55 lbs)
- third physician to conduct examinations, consultations, laboratory tests and discussions with prior physicians as necessary to resolve disagreement
- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow, procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas
- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- the overall status of implementation of the provisions of this Part relating to the identification, inventory, and removal of underwater obstructions
- activities involving the removal of TSI and surfacing ACM and PACM
- repair and maintenance operations, where ACM, including TSI and surfacing ACM and PACM, is likely to be disturbed