

Fire Protection (Subpart F)

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- body belts or harnesses may be used
- rigged to allow the movement of employees only as far as the sides of the working level or working area
- Helmet
- fall restraint systems as approved fall protection method

Cal/OSHA T8 Section 1670(a)

- 100 pounds applied at any point
- requirements of Section 1670
- at 202-366-8075, or electronically to informationresourcesmanager@dot.gov to make arrangements for submitting a report that is due after a request for alternative reporting is submitted but before an authorization or denial is received
- in writing, an alternative reporting method
- data on pipeline facilities abandoned after October 10, 2000 to the National Pipeline Mapping System (NPMS) in accordance with the NPMS Standards
- Table E-1 in § 1915.118
- Fire Alarm System
- Fire Extinguisher
- Fire Brigade
- Fire Protection Program
- where shower facilities are available, that employees shower at the end of the work shift and shall provide an adequate supply of cleansing agents and towels for use by affected employees
- an alternative compliant valve within 7 calendar days of the finding
- at 5 m.p.h. above the requested speed
- interim response plan to maintain safety while repairs are being made
- as soon as practicable within seven calendar days
- compatible and integrated with the disaster, fire and/or emergency response plans of local, state, and federal agencies
- the Commissioner of Conservation for a public hearing for the purpose of establishing rules and regulations and the creation of drilling units for each such pool
- ergonomic program when 2+ employees report repetitive motion injuries from same work activity within 12 months, diagnosed by licensed physician

Cal/OSHA Title 8 Section 5110

- California T8 CCR 5110 mandates the establishment of a formal ergonomic program as an integral part of the overall Injury and Illness Prevention Program (IIPP). This requirement is specifically aimed at reducing the occurrence of repetitive motion...

T8 CCR 5110

- less than 20 pounds per square foot in addition to the weight of the concrete
- 8 hours of refresher training annually
- repetitive motion injury program - no federal equivalent

Cal/OSHA T8 Section 5110

- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow, procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas
- repetitive motion injury prevention program required

T8 CCR 5110

- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- part of the hoisting equipment and meet the requirements of the General Industry Safety Orders
- in a location accessible to the fueling area
- for use when temporary heating devices are used
- 6:BC or larger
- a copy of any surface use agreement
- the terms of any surface use agreement
- Commission at least twenty-four (24) hours notice prior to installation of underground electrical conductors outside of its facilities, fenced enclosures, or posted areas
- six (6) if the number proposed exceeds the Commission's capacity to provide appropriate inspection oversight
- one-half (1/2) charge in the case of bad caps or lead wires

Monday Safety — Sample Document

FEDERAL OSHA REQUIREMENTS

- Fire Extinguisher

1926.150(c)(1)(i)

- Fire Protection Program

1926.150(a)(1)

- each hoist house

29 CFR 1926.552

- within 100 feet travel distance on each floor and within one floor of combustible storage

29 CFR 1926.150(c)(1)(i)-(vi)

- NFPA 10A-1970 - Portable Fire Extinguisher Maintenance

1926.150(c)(1)(viii)

- 100 feet from any point of the protected area

29 CFR 1926.150(c)(1)(i)

Monday Safety — Sample Document

COMPANY PROCEDURES

Guy's Construction implements the following procedures for fire protection (subpart f):

- Guy's Construction shall: Fire Extinguisher

1926.150(c)(1)(i)

- Guy's Construction shall: Fire Protection Program

1926.150(a)(1)

- Guy's Construction shall: each hoist house

29 CFR 1926.552

- Guy's Construction shall: within 100 feet travel distance on each floor and within one floor of combustible storage

29 CFR 1926.150(c)(1)(i)-(vi)

- Guy's Construction shall: 100 feet from any point of the protected area

29 CFR 1926.150(c)(1)(i)

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

California STATE-SPECIFIC REQUIREMENTS (FULL)

- body belts or harnesses may be used
- rigged to allow the movement of employees only as far as the sides of the working level or working area
- Helmet
- fall restraint systems as approved fall protection method

Cal/OSHA T8 Section 1670(a)

- 100 pounds applied at any point
- requirements of Section 1670
- at 202-366-8075, or electronically to informationresourcesmanager@dot.gov to make arrangements for submitting a report that is due after a request for alternative reporting is submitted but before an authorization or denial is received
- in writing, an alternative reporting method
- data on pipeline facilities abandoned after October 10, 2000 to the National Pipeline Mapping System (NPMS) in accordance with the NPMS Standards
- Table E-1 in § 1915.118
- Fire Alarm System
- Fire Extinguisher
- Fire Brigade
- Fire Protection Program
- where shower facilities are available, that employees shower at the end of the work shift and shall provide an adequate supply of cleansing agents and towels for use by affected employees
- an alternative compliant valve within 7 calendar days of the finding
- at 5 m.p.h. above the requested speed
- interim response plan to maintain safety while repairs are being made
- as soon as practicable within seven calendar days
- compatible and integrated with the disaster, fire and/or emergency response plans of local, state, and federal agencies
- the Commissioner of Conservation for a public hearing for the purpose of establishing rules and regulations and the creation of drilling units for each such pool
- ergonomic program when 2+ employees report repetitive motion injuries from same work activity within 12 months, diagnosed by licensed physician

Cal/OSHA Title 8 Section 5110

- California T8 CCR 5110 mandates the establishment of a formal ergonomic program as an integral part of the overall Injury and Illness Prevention Program (IIPP). This requirement is specifically aimed at reducing the occurrence of repetitive motion injuries through systematic evaluation and...

T8 CCR 5110

- less than 20 pounds per square foot in addition to the weight of the concrete
- 8 hours of refresher training annually
- repetitive motion injury program - no federal equivalent

Cal/OSHA T8 Section 5110

- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow,

procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas

- repetitive motion injury prevention program required

T8 CCR 5110

- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- part of the hoisting equipment and meet the requirements of the General Industry Safety Orders
- in a location accessible to the fueling area
- for use when temporary heating devices are used
- 6:BC or larger
- a copy of any surface use agreement
- the terms of any surface use agreement
- Commission at least twenty-four (24) hours notice prior to installation of underground electrical conductors outside of its facilities, fenced enclosures, or posted areas
- six (6) if the number proposed exceeds the Commission's capacity to provide appropriate inspection oversight
- one-half (1/2) charge in the case of bad caps or lead wires

Monday Safety — Sample Document