

HAZWOPER Program

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- decontamination procedures
- 24-hour + 1 day field
- 8 additional hours
- 8-hour
- 8-hour annual refresher
- fiberboard box (4G) or fiber drum (1G) with plastic inner packaging not exceeding 5 kg (11 lbs) and maximum net mass not more than 25 kg (55 lbs)
- the overall status of implementation of the provisions of this Part relating to the identification, inventory, and removal of underwater obstructions
- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow, procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas
- third physician to conduct examinations, consultations, laboratory tests and discussions with prior physicians as necessary to resolve disagreement
- HAZWOPER Trained Personnel
- non-mandatory examples of tests to evaluate compliance with § 1926.65(g)(4)(ii) and (iii)
- Medical Surveillance Program
- Buddy System
- Decontamination Procedures
- response time of 30 minutes or less
- the use of reclaimed water in oil and gas operations
- an operable 360-degree intermittent warning light or beacon mounted on the outside of the vehicle
- each phase of the drill response to validate total response time including rupture identification and valve shut-off \leq 30 minutes
- each valve from unauthorized operation and from vandalism
- the use of Level A and Level B PPE protection
- written safety and health program identifying hazards, employee training, medical surveillance, site control
- Paragraph 1910.120(q)(3)(ii)
- 29 CFR 1910.120 (p)
- overhead protective covering of two-inch planking, 3/4-inch plywood or other solid material of equivalent strength on the top
- medical removal protection benefits to the employee equal to that required by paragraph (n)(9)(v) of this section
- at least eight hours before the mechanical integrity test is conducted
- all applications for plugging extensions that meet the requirements of Commission rules
- the use of live line tools
- clean and sanitary condition

- adequate supply of water sufficient for effective removal of hazardous substance from skin
- potentially hazardous exposure levels
- its permissible exposure limit published in section 5155
- substance technical guidelines and data sheet
- at least two effective means of communication (at least one of which shall be voice communication)
- effective means to communicate the need for and to obtain emergency assistance
- upon initial entry of each shift to the underground and as often as necessary thereafter to ensure proper operation
- data from the analysis and testing required by Paragraphs C.1. and 2 with applicable internal corrosion leak records, incident reports, safety-related condition reports, repair records, patrol records, exposed pipe reports, and test records
- blowout preventer systems and/or diverter systems

Monday Safety — Sample Document

FEDERAL OSHA REQUIREMENTS

- at least 8 hours of hands-on training
- review of confined-space hazards and procedures
- review of hazard communication programs meeting 29 CFR 1910.1200
- review of applicable appendices to 29 CFR 1926.65
- HAZWOPER Trained Personnel

1926.65(e)

- clean-up operations required by a governmental body involving hazardous substances conducted at uncontrolled hazardous waste sites

29 CFR 1910.120(a)(1)(i)

- hazardous waste operations (cleanup, TSD facilities, emergency response) and emergency response to hazmat releases

29 CFR 1910.120(a)

- hazardous waste as defined

Monday Safety — Sample Document

COMPANY PROCEDURES

Guy's Construction implements the following procedures for hazwoper program:

- Guy's Construction shall: at least 8 hours of hands-on training
- Guy's Construction shall: review of confined-space hazards and procedures
- Guy's Construction shall: review of hazard communication programs meeting 29 CFR 1910.1200
- Guy's Construction shall: review of applicable appendices to 29 CFR 1926.65
- Guy's Construction shall: HAZWOPER Trained Personnel

1926.65(e)

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

Monday Safety — Sample Document

California STATE-SPECIFIC REQUIREMENTS (FULL)

- decontamination procedures
- 24-hour + 1 day field
- 8 additional hours
- 8-hour
- 8-hour annual refresher
- fiberboard box (4G) or fiber drum (1G) with plastic inner packaging not exceeding 5 kg (11 lbs) and maximum net mass not more than 25 kg (55 lbs)
- the overall status of implementation of the provisions of this Part relating to the identification, inventory, and removal of underwater obstructions
- a list of interested parties (those with interests in the leases and/or units from which production is to be commingled for which the applicant has no existing commingling authority)
- a diagrammatic sketch of the mechanical installation along with a detailed explanation of the flow, procedures and frequency of well tests, calibration/proving of metering devices and allocation formulas
- third physician to conduct examinations, consultations, laboratory tests and discussions with prior physicians as necessary to resolve disagreement
- HAZWOPER Trained Personnel
- non-mandatory examples of tests to evaluate compliance with § 1926.65(g)(4)(ii) and (iii)
- Medical Surveillance Program
- Buddy System
- Decontamination Procedures
- response time of 30 minutes or less
- the use of reclaimed water in oil and gas operations
- an operable 360-degree intermittent warning light or beacon mounted on the outside of the vehicle
- each phase of the drill response to validate total response time including rupture identification and valve shut-off \leq 30 minutes
- each valve from unauthorized operation and from vandalism
- the use of Level A and Level B PPE protection
- written safety and health program identifying hazards, employee training, medical surveillance, site control
- Paragraph 1910.120(q)(3)(ii)
- 29 CFR 1910.120 (p)
- overhead protective covering of two-inch planking, 3/4-inch plywood or other solid material of equivalent strength on the top
- medical removal protection benefits to the employee equal to that required by paragraph (n)(9)(v) of this section
- at least eight hours before the mechanical integrity test is conducted
- all applications for plugging extensions that meet the requirements of Commission rules
- the use of live line tools
- clean and sanitary condition
- adequate supply of water sufficient for effective removal of hazardous substance from skin

- potentially hazardous exposure levels
- its permissible exposure limit published in section 5155
- substance technical guidelines and data sheet
- at least two effective means of communication (at least one of which shall be voice communication)
- effective means to communicate the need for and to obtain emergency assistance
- upon initial entry of each shift to the underground and as often as necessary thereafter to ensure proper operation
- data from the analysis and testing required by Paragraphs C.1. and 2 with applicable internal corrosion leak records, incident reports, safety-related condition reports, repair records, patrol records, exposed pipe reports, and test records
- blowout preventer systems and/or diverter systems

Monday Safety — Sample Document