

Safety Committee & Meeting

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- critically centered
- eye or face protection be worn when the powder-actuated tool is in use
- line set 3 and should see at least parts of 4 and 5 but not see line set 6 or 6
- Eye or face protection be worn by operators and assistants when the tool is in use
- the lawful market demand for that reservoir
- material which results from activities associated with the exploration, development, or production of oil or gas or geothermal resources and other substance or material regulated by the Railroad Commission of Texas pursuant to Section 91.101,...
- notice to the particular operator(s), lessee(s) of record, or owner(s) of record of unleased mineral interest
- eye or face protection
- high-temperature or carbon monoxide alarm, or both, to monitor carbon monoxide levels
- carbon monoxide poisoning or asphyxiation
- 1,478
- a filing fee of fifty dollars (\$50)
- each end of the runway directly on or as near as practicable to the runway designation numbers
- the end of the line to prevent it from running through the block
- either the appropriate proper shipping name or an appropriate proper shipping name authorized by § 172.101 in effect on December 31, 2014
- establishing and enforcing the CSPP
- 1926.102
- daily pre-task safety briefing covering that day's hazards, controls, and any changed conditions; documented with sign-in sheets; many GCs require documented weekly toolbox talks minimum

29 CFR 1926.21 + industry practice

- "toolbox" or "tailgate" safety meetings, or equivalent, with their crews at least every 10 working days to emphasize safety
- toolbox meetings every 10 working days

Cal/OSHA T8 Section 1509(e)

- toolbox safety meetings at least every 10 working days

Cal/OSHA T8 Section 1509(e)

- toolbox or tailgate safety meetings at least every 10 working days
- a condition when the actual rail temperature is below the rail neutral temperature at or near a joint where longitudinal tensile forces may affect the fastenings at the joint
- or give advice regarding the report of the Board's decision in any proceeding noticed pursuant to NAC 618.650 to 618.848 inclusive
- only the lower portion of a trench is shored and the remaining portion of the trench is sloped or benched unless the slope portion is sloped at an angle less steep than 3 horizontal to one vertical
- vertically sliding gates shall be of the balanced counterweighted type or the biparting counterbalanced type
- exposure to inhalation, ingestion, skin absorption, or contact with any material or substance at a

concentration above those specified in chapter 296-841 WAC

Monday Safety — Sample Document

FEDERAL OSHA REQUIREMENTS

- training verification (OSHA 10/30 cards, competent person designations, equipment certifications), toolbox talk schedule, safety meeting frequency

Industry SSSP templates

Monday Safety — Sample Document

COMPANY PROCEDURES

Guy's Construction implements the following procedures for safety committee & meeting:

- Guy's Construction shall: training verification (OSHA 10/30 cards, competent person designations, equipment certifications), toolbox talk schedule, safety meeting frequency

Industry SSSP templates

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

Monday Safety — Sample Document

California STATE-SPECIFIC REQUIREMENTS (FULL)

- critically centered
- eye or face protection be worn when the powder-actuated tool is in use
- line set 3 and should see at least parts of 4 and 5 but not see line set 6 or 6
- Eye or face protection be worn by operators and assistants when the tool is in use
- the lawful market demand for that reservoir
- material which results from activities associated with the exploration, development, or production of oil or gas or geothermal resources and other substance or material regulated by the Railroad Commission of Texas pursuant to Section 91.101, Natural Resources Code
- notice to the particular operator(s), lessee(s) of record, or owner(s) of record of unleased mineral interest
- eye or face protection
- high-temperature or carbon monoxide alarm, or both, to monitor carbon monoxide levels
- carbon monoxide poisoning or asphyxiation
- 1,478
- a filing fee of fifty dollars (\$50)
- each end of the runway directly on or as near as practicable to the runway designation numbers
- the end of the line to prevent it from running through the block
- either the appropriate proper shipping name or an appropriate proper shipping name authorized by § 172.101 in effect on December 31, 2014
- establishing and enforcing the CSCP
- 1926.102
- daily pre-task safety briefing covering that day's hazards, controls, and any changed conditions; documented with sign-in sheets; many GCs require documented weekly toolbox talks minimum

29 CFR 1926.21 + industry practice

- "toolbox" or "tailgate" safety meetings, or equivalent, with their crews at least every 10 working days to emphasize safety
- toolbox meetings every 10 working days

Cal/OSHA T8 Section 1509(e)

- toolbox safety meetings at least every 10 working days

Cal/OSHA T8 Section 1509(e)

- toolbox or tailgate safety meetings at least every 10 working days
- a condition when the actual rail temperature is below the rail neutral temperature at or near a joint where longitudinal tensile forces may affect the fastenings at the joint
- or give advice regarding the report of the Board's decision in any proceeding noticed pursuant to NAC 618.650 to 618.848 inclusive
- only the lower portion of a trench is shored and the remaining portion of the trench is sloped or benched unless the slope portion is sloped at an angle less steep than 3 horizontal to one vertical
- vertically sliding gates shall be of the balanced counterweighted type or the biparting counterbalanced type
- exposure to inhalation, ingestion, skin absorption, or contact with any material or substance at a concentration above those specified in chapter 296-841 WAC