

Stairways & Ladders

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- building or structure has only one stairway between levels
- hazardous projections such as protruding nails
- before the stairway is used to reach another level
- before stairway is used
- stairway is used before slippery conditions are eliminated
- Fall protection must be provided at four feet or more
- November 10, 2017
- 380 mm (15 in.) from the electric arc
- specific arrangement approved by the Regional Administrator
- minimum approach distance established under § 1910.269(l)(3)(i) is greater than or equal to the values listed for voltages >72.6 kV (72.6-121.0 kV: 1.02 m; 121.1-145.0 kV: 1.16 m; 145.1-169.0 kV: 1.30 m; 169.1-242.0 kV: 1.72 m; 242.1-362.0 kV: 2.76...
- bear on the side rails in addition to the ladder rungs
- the side rails in addition to the ladder rungs
- additional requirements

CA T8 1675

- side rails in addition to the ladder rungs
- 10 feet
- Drilling Rig Contractor Name, Rig Number and Rig Kelley Bushing Height feet
- all activities involving the manufacture, handling or storage of ammonium perchlorate in this State
- destination of waste oil or waste oil residue as reported by transporter
- Option 15
- 29 CFR 1926.1050 Scope, application and definitions applicable to this Subdivision, published 8/9/10, FR vol. 75, no. 152, pp. 47906-48177
- 29 CFR 1926.1050
- 29 CFR 1926.1050 Scope, application and definitions applicable to this Subdivision
- compliance with 29 CFR 1926.1050-1053 general requirements and design criteria
- revised paragraph (a) in 1926.1050
- 150 feet per minute
- each phase of the drill response to validate total response time including rupture identification and valve shut-off ≤ 30 minutes
- the use of reclaimed water in oil and gas operations
- for each abandoned offshore pipeline facility or each abandoned onshore pipeline facility that crosses over, under or through commercially navigable waterways in accordance with § 195.59
- an agreement with the Surety Department for the Conservation Division to properly close and reclaim the site in accordance with approved procedures, on forms available from the Conservation Division and accompanied by surety
- 29 CFR 1926.1052 Stairways, published 8/23/91, FR vol. 56, no. 164, pp. 41793-41794

- 29 CFR 1926.1052
- 29 CFR 1926.1052
- 29 CFR 1926.1052 Stairways
- a medical surveillance program in accordance with paragraphs (j)(2) and (j)(3) of this section for all employees who are or may be exposed by the employer at or above the action level for more than 30 days in any consecutive 12 months
- all medical examinations and procedures are performed by or under the supervision of a licensed physician
- as free as practicable of accumulations of lead
- 5.0 seconds when the equipment is deenergized

Monday Safety — Sample Document

FEDERAL OSHA REQUIREMENTS

- a tower comprised of scaffold components and which contains internal stairway units and rest platforms

29 CFR 1926.450

- 30 to 50 degree angle from horizontal

29 CFR 1926.1052(a)(2)

- Ladder/Stairway Training by Competent Person

1926.1060(a)(1)

- retraining until proficiency regained

29 CFR 1926.1060(b)

- Guardrail Systems

1926.1052(c)(12)

- parallel, level, and uniformly spaced when the ladder is in position for use

29 CFR 1926.1053(a)(2)

- a marine ladder of rope or chain with wooden or metal rungs

29 CFR 1926.606(d)

- a double-cleated ladder or two or more separate ladders

29 CFR 1926.1051(a)(2)

- 250-Pound Load Between Each Consecutive Attachment

1926.1053(a)(1)(iii)

- 29 CFR 1926.1050

- 29 CFR 1926.1050 Scope, application and definitions applicable to this Subdivision

- compliance with 29 CFR 1926.1050-1053 general requirements and design criteria

- revised paragraph (a) in 1926.1050

- 29 CFR 1926.1052 Stairways, published 8/23/91, FR vol. 56, no. 164, pp. 41793-41794

- 29 CFR 1926.1052

Monday Safety — Sample Document

COMPANY PROCEDURES

Guy's Construction implements the following procedures for stairways & ladders:

- Guy's Construction shall: 30 to 50 degree angle from horizontal

29 CFR 1926.1052(a)(2)

- Guy's Construction shall: Ladder/Stairway Training by Competent Person

1926.1060(a)(1)

- Guy's Construction shall: retraining until proficiency regained

29 CFR 1926.1060(b)

- Guy's Construction shall: Guardrail Systems

1926.1052(c)(12)

- Guy's Construction shall: parallel, level, and uniformly spaced when the ladder is in position for use

29 CFR 1926.1053(a)(2)

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

Monday Safety — Sample Document

California STATE-SPECIFIC REQUIREMENTS (FULL)

- building or structure has only one stairway between levels
- hazardous projections such as protruding nails
- before the stairway is used to reach another level
- before stairway is used
- stairway is used before slippery conditions are eliminated
- Fall protection must be provided at four feet or more
- November 10, 2017
- 380 mm (15 in.) from the electric arc
- specific arrangement approved by the Regional Administrator
- minimum approach distance established under § 1910.269(l)(3)(i) is greater than or equal to the values listed for voltages >72.6 kV (72.6-121.0 kV: 1.02 m; 121.1-145.0 kV: 1.16 m; 145.1-169.0 kV: 1.30 m; 169.1-242.0 kV: 1.72 m; 242.1-362.0 kV: 2.76 m; 362.1-420.0 kV: 2.50 m; 420.1-550.0 kV: 3.62 m;...
- bear on the side rails in addition to the ladder rungs
- the side rails in addition to the ladder rungs
- additional requirements

CA T8 1675

- side rails in addition to the ladder rungs
- 10 feet
- Drilling Rig Contractor Name, Rig Number and Rig Kelley Bushing Height feet
- all activities involving the manufacture, handling or storage of ammonium perchlorate in this State
- destination of waste oil or waste oil residue as reported by transporter
- Option 15
- 29 CFR 1926.1050 Scope, application and definitions applicable to this Subdivision, published 8/9/10, FR vol. 75, no. 152, pp. 47906-48177
- 29 CFR 1926.1050
- 29 CFR 1926.1050 Scope, application and definitions applicable to this Subdivision
- compliance with 29 CFR 1926.1050-1053 general requirements and design criteria
- revised paragraph (a) in 1926.1050
- 150 feet per minute
- each phase of the drill response to validate total response time including rupture identification and valve shut-off <= 30 minutes
- the use of reclaimed water in oil and gas operations
- for each abandoned offshore pipeline facility or each abandoned onshore pipeline facility that crosses over, under or through commercially navigable waterways in accordance with § 195.59
- an agreement with the Surety Department for the Conservation Division to properly close and reclaim the site in accordance with approved procedures, on forms available from the Conservation Division and accompanied by surety
- 29 CFR 1926.1052 Stairways, published 8/23/91, FR vol. 56, no. 164, pp. 41793-41794
- 29 CFR 1926.1052

- 29 CFR 1926.1052
- 29 CFR 1926.1052 Stairways
- a medical surveillance program in accordance with paragraphs (j)(2) and (j)(3) of this section for all employees who are or may be exposed by the employer at or above the action level for more than 30 days in any consecutive 12 months
- all medical examinations and procedures are performed by or under the supervision of a licensed physician
- as free as practicable of accumulations of lead
- 5.0 seconds when the equipment is deenergized

Monday Safety — Sample Document