

State Construction Permits

Guy's Construction
123 Main Street, Anytown, CA 90210

Ontology-Backed Safety Document

Effective Date: June 08, 2026

SAMPLE DOCUMENT - NOT FOR COMPLIANCE USE

JURISDICTION AND REGULATORY FRAMEWORK

STATE-SPECIFIC: California has the following requirements:

- Confined Space Entry Permit under §5157 - permit required for excavation depth alone regardless of atmospheric hazards
- any additional permits such as for hot work that have been issued to authorize work in the permit space
- the permit space to be entered
- the time required to complete the assigned task or job identified on the permit
- written or printed document provided by the employer to allow and control entry into a permit space containing the information specified in subsection (f)
- a sheet metal jacket of not less than 16 gauge thickness (when insulation remains effective under fire conditions)
- minimize the possibility of tampering
- gas-tight plugs or caps
- May 1, 2025 for unrefined petroleum products
- April 1, 2020 for unrefined petroleum products
- cadmium or materials containing cadmium are present
- identify the permit space to be entered
- separate physical establishments requiring a separate notice or notices to be posted in each
- Personal belongings must be stored in such a manner as to not interfere with access or operation of the crane
- fails to comply with the requirements of 803 KAR 2:080 pursuant to KRS 338.991
- at each exception level as defined in the GRMS parameters table
- each establishment in a conspicuous place or places where notices to employees are customarily posted
- Operating between 0 and 10 miles per hour over hard clay where rollover would be limited to a maximum roll angle of 360° down a slope of 30° maximum
- Test setup shown in FIGURE V-2 for rollover protective structures (ROPS)
- more than 20 engine horsepower
- Oregon Department
- exceeds 50 µg/dl on two tests triggers monthly BLL tests during temporary removal

FEDERAL OSHA REQUIREMENTS

- the employer's written authorization to perform operations capable of providing a source of ignition

29 CFR 1910.146

- employer's written authorization to perform operations capable of providing a source of ignition
- hot work permit listed on entry permit

29 CFR 1926.1206(p)

- Written Permit Space Program

1926.1203(d)

- hot work permit, fire watch during and 30 min after, combustibles removed 35 ft or covered with fire-resistant material, fire extinguisher available, confined space precautions if applicable

29 CFR 1910.252(a), 1926.352-354

Monday Safety — Sample Document

COMPANY PROCEDURES

Guy's Construction implements the following procedures for state construction permits:

- Guy's Construction shall: hot work permit listed on entry permit

29 CFR 1926.1206(p)

- Guy's Construction shall: Hot Work Permit

1926.1206(p)

- Guy's Construction shall: Written Permit Space Program

1926.1203(d)

- Guy's Construction shall: hot work permit, fire watch during and 30 min after, combustibles removed 35 ft or covered with fire-resistant material, fire extinguisher available, confined space precautions if applicable

29 CFR 1910.252(a), 1926.352-354

TRAINING REQUIREMENTS

- All employees involved in this scope of work must receive initial training before beginning work
- Refresher training when procedures change or deficiencies are observed
- Training must be documented with date, topic, trainer, and attendees

RECORDKEEPING

- Training records: duration of employment
- Inspection/monitoring records: project duration + 3 years
- Incident reports: 5 years

Monday Safety — Sample Document

California STATE-SPECIFIC REQUIREMENTS (FULL)

- Confined Space Entry Permit under §5157 - permit required for excavation depth alone regardless of atmospheric hazards
- any additional permits such as for hot work that have been issued to authorize work in the permit space
- the permit space to be entered
- the time required to complete the assigned task or job identified on the permit
- written or printed document provided by the employer to allow and control entry into a permit space containing the information specified in subsection (f)
- a sheet metal jacket of not less than 16 gauge thickness (when insulation remains effective under fire conditions)
- minimize the possibility of tampering
- gas-tight plugs or caps
- May 1, 2025 for unrefined petroleum products
- April 1, 2020 for unrefined petroleum products
- cadmium or materials containing cadmium are present
- identify the permit space to be entered
- separate physical establishments requiring a separate notice or notices to be posted in each
- Personal belongings must be stored in such a manner as to not interfere with access or operation of the crane
- fails to comply with the requirements of 803 KAR 2:080 pursuant to KRS 338.991
- at each exception level as defined in the GRMS parameters table
- each establishment in a conspicuous place or places where notices to employees are customarily posted
- Operating between 0 and 10 miles per hour over hard clay where rollover would be limited to a maximum roll angle of 360° down a slope of 30° maximum
- Test setup shown in FIGURE V-2 for rollover protective structures (ROPS)
- more than 20 engine horsepower
- Oregon Department
- exceeds 50 µg/dl on two tests triggers monthly BLL tests during temporary removal